

IN THE CLAIMS:

The following is a complete listing of the claims, and replaces all earlier listings and all earlier versions.

- 5.6 B, >
- A1
1. (Currently Amended) An image processing apparatus comprising:
rendering means for rendering data in a first color space and data in a second color space; and
a plurality of image forming means for forming images in units of colors of the rendered image data,
wherein said rendering means performs band mapping of data if band mapping is possible, and
wherein, when band mapping is impossible in said rendering means, said apparatus informs a host computer to which said apparatus is connected that the band mapping is impossible.
 2. (Original) The apparatus according to claim 1, wherein the first and second color spaces are respectively RGB and YMCK spaces.
 3. (Original) The apparatus according to claim 1, wherein the plurality of image forming means form Y, M, C, and K images.

4. (Currently Amended) The apparatus according to claim 1, further comprising conversion means for converting the data in the first color space into data in the second color space, and

wherein said image forming means forms an image based on one of data rendered in the second color space by said rendering means and data converted by said conversion means.

5. and 6. (Canceled)

5
7. (Currently Amended) The apparatus according to claim 1, wherein when the band mapping is impossible in said rendering means, said apparatus processes data to have a format with which the band mapping is possible.

6
8. (Original) The apparatus according to claim 1, wherein said rendering means simultaneously renders a plurality of color data upon rendering data in the first color space, and renders a plurality of color data in turn upon rendering image data in the second color space.

7
9. (Original) The apparatus according to claim 1, wherein image formation using data in the second color space assures higher quality than image formation using data in the first color space.

7 10. (Currently Amended) An image processing method comprising the steps of:

~~the rendering step of rendering data in a first color space and data in a second color space; and~~

~~the image forming step of forming images of the rendered image data in units of colors,~~

~~wherein said rendering step includes performing band mapping of data if band mapping is possible, and~~

~~wherein, when band mapping is impossible in said rendering step, notification is sent to a host computer to which an apparatus performing said method is connected, the notification stating that the band mapping is impossible.~~

9 11. (Currently Amended) A storage medium storing a program which comprising:

a code of ~~[[the]]~~ a step of rendering data in a first color space and data in a second color space; and

a code of ~~[[the]]~~ a step of forming images of the rendered image data in units of colors,

~~wherein said rendering step includes performing band mapping of data if band mapping is possible, and~~

~~wherein, when band mapping is impossible in said rendering step, notification is sent to a host computer to which an apparatus performing said method is connected, the notification stating that the band mapping is impossible.~~

12. - 30. (Canceled).

5.5 B.1 } 10 31. (New) An image processing apparatus capable of forming an image based on image data in RGB or YMCK format transmitted from an information processing apparatus, said image processing apparatus comprising:

holding means for holding the image data transmitted;

rendering means for acquiring the image data held in said holding means in units of colors by accessing said holding means via a bus, and generating rendering data;

image forming means for forming an image in units of colors based on the rendering data; and

7. determining means for, when a format of the image data is RGB format, predicting the rendering time for generating the rendering data in the RGB format based on the load of bus for acquiring the image data in the RGB format in units of colors, and determining whether or not it is possible to generate the rendering data,

wherein, if it is determined by said determining means that it is not possible to generate the rendering data, an image in YMCK format is formed by demanding that the information processing apparatus transmits image data in YMCK format.

11 32. (New) The apparatus according to claim 31, further comprising 10 converting means for converting the rendering data in RGB format into a rendering data in YMCK format,

71 wherein said image forming means forms an image, in units of colors, based on the rendering data in YMCK format generated by said rendering means or the rendering data in YMCK format converted by said converting means.
